

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/00524 A1

- (51) International Patent Classification⁷: C01B 3/40, WAILES, David [GB/GB]; 4 Whitecotes Park, Chesterfield, Derbyshire S40 3RT (GB).
3/32, B01J 38/06, 38/04
- (21) International Application Number: PCT/GB00/02387 (74) Agent: WISHART, Ian, Carmichael; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NH (GB).
- (22) International Filing Date: 20 June 2000 (20.06.2000)
- (25) Filing Language: English (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (26) Publication Language: English
- (30) Priority Data: 9914662.3 24 June 1999 (24.06.1999) GB (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): JOHN-SON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): BURCH, Robert [GB/GB]; 34 Belfast Road, Antrim BT41 1PB (GB). GOLUNSKI, Stanislaw, Edmund [GB/GB]; 2 Widmore Lane, Sonning Common, Reading RG4 9RR (GB). SOUTHWARD, Barry, William, Luke [GB/GB]; 19 Ardmore Avenue, Ormeau, Belfast BT7 3HD (GB).
- Published:
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 01/00524 A1

(54) Title: PROCESS FOR THE REGENERATION OF REFORMING CATALYSTS

(57) Abstract: The present invention relates to methods for the regeneration of catalytic reactors. In particular it relates to methods for regenerating a fuel-processing catalyst whilst it is still being used to supply hydrogen to a fuel cell. The temperature of the catalyst may be adjusted, the air, steam or fuel feed rate may be adjusted. Alternatively, additives may be added to the feed.

PROCESS FOR THE REGENERATION OF REFORMING CATALYSTS

The present invention relates to methods for the regeneration of catalytic reactors.

5

Catalytic converters are frequently used in internal combustion engines in order to meet the various regulations concerning the levels of pollutants in exhaust gases. A three-way catalyst is a common form of converter used. This has three main duties, namely, the oxidation of CO, the oxidation of unburnt hydrocarbons (HC's) and the reduction of NOx to N₂. Such catalysts require careful engine management to ensure that the engine operates at or close to stoichiometric conditions, that is fuel/air $\lambda=1$. Growing awareness of the need to conserve the earth's resources and increasingly stringent legislation have recently prompted a search for cleaner and more efficient alternatives to the internal combustion engine. One of the most promising of these is the combination of an electric motor and a fuel cell. However, the latter requires a source of hydrogen, for which there is no supply and distribution infrastructure comparable to that for liquid fuels.

10

15

The use of fuel cells is not just limited to vehicle applications. Emergent markets include domestic co-generation of heat and power, and power generation in remote locations. Again, the availability of hydrogen is a key issue, with natural gas often being the preferred fuel for domestic systems, and liquid hydrocarbons being more transportable to remote locations.

20

The problems of hydrogen supply and distribution can be overcome by generating it within the fuel-cell system. A hydrogen-rich gas stream, commonly known as 'reformat', can be produced by catalytically converting organic fuels (such as gasoline, natural gas or alcohol). The process, which is referred to as 'reforming' or 'fuel-processing', can occur by a number of different reaction mechanisms :

25

- 30 - dissociation (splitting of the fuel molecules),
- steam reforming (reaction of the fuel with H₂O),
- partial oxidation (reaction of the fuel with O₂, usually supplied as air)
- combinations of the above reactions.

Because the performance of the reformer has a direct effect on the power output from the fuel cell, deactivation of the catalyst cannot be allowed to proceed unchecked. However the process of power generation cannot be stopped to allow regeneration of the reformer, when its performance falls below an acceptable level. The regeneration of such catalytic reactors whilst they are in use is the problem this invention sets out to solve.

In many instances, the performance of the catalyst declines while it is being used. Although the rate of decline can usually be reduced by changing the operating conditions, it is often accompanied by a drop in hydrogen and power output. One frequently practised method for restoring the performance of a fuel processor is to replace the catalyst periodically. Another method involves regenerating the catalyst while it remains in the processor, using a prescribed regeneration procedure (eg see JR Rostrup-Nielsen in *Catalysis Today*, Vol 37, 1997, p 225-232). However, both these require that the process of hydrogen-generation is interrupted in order to restore performance.

Thus in a first aspect, the present invention provides a method for regenerating a catalytic fuel processor, while it is being used to supply hydrogen to a fuel cell, comprising any one or more of the steps of:

20

- continuing to pass fuel, air and steam through a reforming catalyst whilst the catalyst is heated by an external heat source such that the temperature of the catalyst may be adjusted,
- continuing to pass fuel, air and steam through a reforming catalyst and modulating the air and/or steam feed rate,
- continuing to pass, air, fuel and steam through a reforming catalyst and modulating the feed-rate of the fuel.
- continuing to pass fuel, air and steam through a reforming catalyst wherein additive is added to the feed.

30

and maintaining the hydrogen concentration in dry reformat above 25% throughout the operation of the processor.

The reforming catalyst may be one component of the catalytic fuel processor, or it may be the only component. Where loss of performance is being caused by a particular component in a complex fuel mixture, the regeneration method can be targeted at the specific deactivating effect.

5

Thus in a second aspect, the present invention provides a method for preventing or retarding the de-activation of a catalytic fuel processor while it is being used to supply hydrogen to a fuel cell comprising any one or more of the steps of:

- 10 - continuing to pass fuel, air and steam through a reforming catalyst whilst the catalyst is heated by an external heat source such that the temperature of the catalyst may be adjusted,
 - continuing to pass fuel, air and steam through a reforming catalyst and modulating the air and/or steam feed rate,
 - 15 - continuing to pass, air, fuel and steam through a reforming catalyst and modulating the feed-rate of the fuel,
 - continuing to pass fuel, air and steam through a reforming catalyst wherein additive is added to the feed.
- 20 and maintaining the hydrogen concentration in dry reformat above 25% throughout the operation of the processor.

Again, the reforming catalyst may be one component or the only component of the catalytic fuel processor. In a preferred embodiment of the invention water is temporarily added to the feed. ('Feed' is a term used to describe the reactant mixture supplied to the fuel processor.) The water will be rapidly converted into steam in the catalyst. The water (steam) to carbon ratio in the feed may readily be adjusted in order to permit targeting of the regeneration method to a specific deactivating event. Adjusted for the purposes of this invention means increased or decreased. The oxygen to carbon ratio
30 may also be adjusted for the same purpose, by adding or changing the feed-rate of air, or by changing the feed-rate of the fuel.

The catalyst may contain one or more base metals, which may include copper (often used for reforming methanol) and nickel (used for reforming natural gas and higher hydrocarbons). Alternatively, the catalyst may contain one or more precious metals, which may include gold, platinum, palladium, iridium, silver, rhodium and ruthenium. Furthermore, it may contain both base metal(s) and precious metal(s). The catalyst may also contain refractory materials, such as ceramics, metal oxides, perovskites, metal carbides and metal sulphides.

Additives may be added to the feed for various purposes, including acceleration of start-up of a fuel-processor, and the prevention or inhibition of its deactivation. Alternatively, a fuel to which additives have been added during manufacture can be used. In a preferred embodiment of the invention, the additive is an oxygenate, and in an especially preferred embodiment the oxygenate is MTBE (methyl-tert-butylether).

In order to facilitate the regeneration procedure, the temperature of the catalyst bed may be raised temporarily by an external energy source. Within a fuel cell system, the external energy source may be an electrical heater, or a burner (which combusts either some of the fuel or some of the hydrogen produced). In addition, or alternatively, the temperature of one or more of the feed components may be raised temporarily, again by an external heat source.

Among the most common causes of deactivation of a fuel-processor is the retention of carbon or sulphur species by the catalyst. Therefore, in a further embodiment of the invention, catalyst regeneration may occur by removal of the carbon or sulphur species. The carbon species originate from the fuel molecules, and indicate the occurrence of undesired side reactions. The sulphur species originate either from indigenous contaminants in the fuel or from compounds deliberately added to the fuel (such as the odourants used to give natural gas its recognisable smell).

The present invention will now be described by way of the following examples in which:

Figure 1a: shows the composition of dry reformat as a function of time during reforming of dodecane (under conditions described in Example 1).

Figure 1b shows the effect of air pulses on the composition of dry reformat during reforming of dodecane (as described in Example 2).

In both cases % in reformat is on the vertical axis and time/hours is on the horizontal axis.

- 5 ♦ represents Hydrogen, ■ represents carbon monoxide, and ▲ represents carbon monoxide.

Figure 2a shows the composition of dry reformat as a function of time during the reforming of toluene under the two conditions described in example 5.

- 10 Figure 2b shows the effect of increasing the air feed-rate on the composition of dry reformat, during reforming of toluene (as described in example 6).

In both cases the left hand side of the vertical axis represents % in reformat and the right hand side of the vertical axis represents temperature in °C. The horizontal axis represents time/hours; ♦ represents hydrogen, ■ represents carbon dioxide,

- 15 ▲ represents carbon monoxide and x represents temperature.

It will be appreciated that many variations can be made to the invention herein described without departing from the present inventive concept.

20 **Example 1 (Aliphatic fuel ; no regeneration)**

- A bed (0.2 g) of reforming catalyst was packed into a tubular quartz reactor, which was positioned at the centre of a furnace. A mixture of dodecane vapour (produced by vaporising the liquid at a rate of $4 \text{ cm}^3 \text{ hour}^{-1}$), air ($200 \text{ cm}^3 \text{ min}^{-1}$) and
25 steam (produced by vaporising water at a rate of $4 \text{ cm}^3 \text{ hour}^{-1}$) was passed through the catalyst bed, which was heated by the furnace. The furnace temperature was maintained at 500°C . The product stream (ie the reformat) passed through a drier before entering a gas chromatograph, which was used to analyse for hydrogen. The initial concentration of hydrogen in the dry reformat was just above 25%, but declined to 20% within an
30 hour, and to 15% within 4 hours. See Figure 1a for results.

Example 2 (Regeneration by air pulses)

The test procedure described in Example 1 was repeated with a fresh charge of catalyst, except that every 10 minutes the air feed-rate was increased to $350 \text{ cm}^3 \text{ min}^{-1}$ for 30 seconds. Apart from the duration of the extra air pulses, the concentration of hydrogen in the dry reformat remained above 25% during 3 hours of testing. See Figure 1b for results.

Example 3 (Regeneration by temperature excursions)

10

The test procedure described in Example 1 was repeated with a fresh charge of catalyst. Whenever the hydrogen concentration in the dry reformat dropped below 25%, it could be restored by raising the furnace temperature to 600°C for 1 minute.

15

Example 4 (Inhibition of de-activation by MTBE addition)

The test procedure described in Example 1 was repeated with a fresh charge of catalyst, except that 10% (by volume) methyl-tert-butylether was added to the dodecane. The hydrogen concentration in the dry reformat remained above 25% throughout 5 hours of testing.

20

Example 5 (Aromatic fuel ; no regeneration)

A bed (0.2 g) of reforming catalyst was packed into a tubular quartz reactor, which was positioned at the centre of a furnace. A mixture of toluene vapour (produced by vaporising the liquid at a rate of $4 \text{ cm}^3 \text{ hour}^{-1}$), air ($175 \text{ cm}^3 \text{ min}^{-1}$) and steam (produced by vaporising water at a rate of $4 \text{ cm}^3 \text{ hour}^{-1}$) was passed through the catalyst bed, which was heated by the furnace. The furnace temperature was maintained at 500°C . The initial concentration of hydrogen in the dry reformat was 33%, but declined to 25% within 3 hours. When the catalyst was replaced by a fresh charge and the feed-rate of steam was doubled (by increasing the rate of vaporising water to 8 cm^3

30

hour⁻¹), the initial concentration of hydrogen in the dry reformat was 37%. Within 3 hours, the hydrogen concentration had declined to 30%. See Figure 2a for results.

Example 6 (Prevention of de-activation by extra air)

5

The test procedure described in Example 5 was repeated with a fresh charge of catalyst, except that the air feed-rate was increased to 200 cm³ min⁻¹. The initial concentration of hydrogen in the dry reformat was 32%. The concentration remained unchanged during 3 hours of testing. See Figure 2b for results.

10

CLAIMS

1. A method for regenerating a catalytic fuel processor, while it is being used to supply hydrogen to a fuel cell, comprising any one or more of the steps of:

5

- continuing to pass fuel, air and steam through a reforming catalyst whilst the catalyst is heated by an external heat source such that the temperature of the catalyst may be adjusted,
- continuing to pass fuel, air and steam through a reforming catalyst and modulating the air and/or steam feed rate,
- 10 - continuing to pass, air, fuel and steam through a reforming catalyst and modulating the feed-rate of the fuel.
- continuing to pass fuel, air and steam through a reforming catalyst wherein additive is added to the feed.

15

and maintaining the hydrogen concentration in dry reformat above 25% throughout the operation of the processor.

2. A method for preventing or retarding the de-activation of a catalytic fuel processor while it is being used to supply hydrogen to a fuel cell comprising any one or more of the steps of:

20

- continuing to pass fuel, air and steam through a reforming catalyst whilst the catalyst is heated by an external heat source such that the temperature of the catalyst may be adjusted,
- 25 - continuing to pass fuel, air and steam through a reforming catalyst and modulating the air and/or steam feed rate,
- continuing to pass air, fuel and steam through a reforming catalyst and modulating the feed-rate of the fuel.
- 30 - continuing to pass fuel, air and steam through a reforming catalyst wherein additive is added to the feed.

and maintaining the hydrogen concentration in dry reformat above 25% throughout the operation of the processor.

3. A method according to either claim 1 or claim 2, whereby water is temporarily
5 added to the fuel.

4. A method according to claims 1 or 2 in which air is temporarily added to the feed.

10 5. A method according to claims 1 or 2 in which an additive is added to the feed.

6. A method according to claim 5 in which the additive is an oxygenate.

7. A method according to claim 6 in which the oxygenate is MTBE
15 (methyl-tert-butylether).

8. A method according to claims 1 or 2 in which the catalyst bed temperature is raised temporarily by an external heat source.

20 9. A method according to claims 1 or 2 in which the temperature of one or more of the reactant feeds is raised temporarily.

25

30

1 / 2




FIG. 1a




FIG. 1b

2/2




FIG. 2a




FIG. 2b

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 00/02387

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C01B3/40 C01B3/32 B01J38/06 B01J38/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C01B B01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, CHEM ABS Data, PAJ, INSPEC, COMPENDEX, API Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 884 271 A (DBB FUEL CELL ENGINES GMBH) 16 December 1998 (1998-12-16) the whole document	1,2,5,8, 9
A	US 4 089 941 A (VILLEMIN BERNARD) 16 May 1978 (1978-05-16) claim 7	1,2
A	US 5 075 268 A (KURASHIGE MITSUHIKO ET AL) 24 December 1991 (1991-12-24) the whole document	1,2
A	US 4 083 799 A (ESTES JOHN HAROLD ET AL) 11 April 1978 (1978-04-11) column 6, line 14 - line 18	1,2
	--- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 September 2000

Date of mailing of the international search report

02/10/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van der Poel, W

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/02387

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 08, 30 June 1999 (1999-06-30) & JP 11 079702 A (TOYOTA CENTRAL RES & DEV LAB INC), 23 March 1999 (1999-03-23) abstract	1,2,4
A	DE 24 03 701 A (BASF AG) 7 August 1975 (1975-08-07) claims	1,2,6
A	US 5 043 518 A (MICHAELSON ROBERT C ET AL) 27 August 1991 (1991-08-27) column 2, line 40 -column 4, line 21	6,7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 00/02387

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0884271	A	16-12-1998	DE 19725007 C	18-03-1999
US 4089941	A	16-05-1978	FR 2328656 A	20-05-1977
			DE 2645522 A	28-04-1977
			DK 476176 A,B,	23-04-1977
			GB 1511789 A	24-05-1978
			JP 52052191 A	26-04-1977
US 5075268	A	24-12-1991	JP 1846686 C	07-06-1994
			JP 4200640 A	21-07-1992
			JP 5081303 B	12-11-1993
US 4083799	A	11-04-1978	NONE	
JP 11079702	A	23-03-1999	NONE	
DE 2403701	A	07-08-1975	NONE	
US 5043518	A	27-08-1991	CA 2064040 A	01-02-1991
			EP 0637994 A	15-02-1995
			JP 4507368 T	24-12-1992
			WO 9101804 A	21-02-1991
			US 5223464 A	29-06-1993